



JAYLAXMI INDUSTRIES
Improvising, Innovating & Evolving

Rabbeth (Bare Blade) Type



Products Spindles: HF-1 , HF-21 , CS1 , CS 21 insert

For Machine:

Reiter, L.R (LMW) LR6, LR8, LR9, LR7 machines, Texaco, KTTM, MMC, Mazroli, Zinser, Textool, suessen ,

For Process Type: cotton industries, man-made fibers, wool, and blends

Product Description

- Material : spindle blade : EN 31 alloy (bearing steel), wharves : EN 24 alloy
- Spindle's wharves diameter 18.5 to 22mm.
- high quality , low vibration, Operating long life
- supplies complete set with flange , nut , spindle lock
- manufacture spindle for ring diameter : 38mm , 40mm , 42mm, 45mm, 48mm etc
- We supplied spindle with specified insert as Texpart, SKF (Teraspin) , Novibra , Jaylaxmi .





Spindle Application

- Jaylaxmi reduce vibration up to 0.05 mm / sec
- Jaylaxmi reduce noise level to 75 DBA
- Operating long life
- Short delivery time

Advantages

- Low noise & Power
- High speed up-to 22,000 rpm.
- Dynamically balanced.
- 5 Stage Quality Checks to ensure exquisite quality system maintenance for superior performance.
- Made to fit your system and give higher and better performance index.

➤ Technical Data Sheet

Type of spindle	Wharves dia (mm)	Lift size (mm)	Insert/bolster		Speed RPM (Mechanical)	Weight in Kgs (S.U.P)
Rabbeth (bare blade) type	18.5 to 22.5	165 to 204	SKF	HF 1	Up to 22,000	0.200 and above
				HF 21	Up to 20,000	
			TEXPART	CS1 CS1 12	Up to 22,000	
				CS 1 S CS 1 S 12	Up to 30,000	

